



for bollard specifications refer to the **BOLLARD HANDBOOK** or visit our website www.l-v.com.au

Installation

- Core drilling into existing ground-based concrete slab of minimum 200mm thickness (slabs less than 200mm may require a new concrete footing), or
- Where slab depth is insufficient or surface is bitumen, pavers and the like, bollards are installed using a sleeve fixed into a reinforced concrete footing.
Refer Installation, p.49 in the Bollard Handbook.

Recommended

Refer Accessories, p.52 in the Bollard Handbook.

Storage Sleeve (2 bollards) – when driveway is in constant use.

Cover Plate – for use when Locking & Removable Bollard is removed.



Leda-Vannaclip Pty Ltd

www.l-v.com.au

toll free 1300 780 450

Head Office & Manufacturing
18 Reliance Drive, Tuggerah 2250
PO Box 5196 Chittaway Bay 2261
Phone +61 2 4353 3377
Fax +61 2 4353 2255

NSW Sales
3/43-51 College St, Gladesville 2111
PO Box 802 Gladesville 1675
Phone +61 2 9817 4799
Fax +61 2 9817 8560

VIC Sales & Manufacturing
18-20 Macaulay St,
Williamstown 3016
Phone +61 3 9397 3233
Fax +61 3 9397 3244

QLD Sales
2/387 Lytton Road,
Morningside 4170
Phone +61 7 3399 5633
Fax +61 7 3399 5688

SA Sales
10 Bennet Ave,
Melrose Park 5039
Phone +61 8 8374 3266
Fax +61 8 8374 3299